Copyright © 2023 University of Cambridge. Not to be quoted or reproduced without permission

1 Revision of main ideas and results from IB Fluids

1.1 Continuum hypothesis

We assume that at every point \mathbf{x} of the fluid and at all times t we can define, by averaging over a small volume, "continuum" properties like density $\rho(\mathbf{x}, t)$, velocity $\mathbf{u}(\mathbf{x}, t)$ and pressure $p(\mathbf{x}, t)$. Here \mathbf{x} refers to a position in the laboratory frame (Eulerian description). We thus do not deal with the dynamics of individual molecules.

1.2 Time derivatives

A fluid particle, sometimes called a material element or a Lagrangian point, is one that moves with the fluid, so that its position $\mathbf{x}(t)$ satisfies

$$\dot{\mathbf{x}} = \mathbf{u}(\mathbf{x}, t).$$

The rate of change of a quantity as seen by a fluid particle is written D/Dt, given by the chain rule as

$$\frac{D}{Dt} \equiv \frac{\partial}{\partial t} + \mathbf{u} \cdot \nabla.$$

This is called the *material* (or *convected* or *substantial*) derivative. In particular, the *acceleration* of a fluid particle is

$$D\mathbf{u}/Dt = \partial \mathbf{u}/\partial t + \mathbf{u} \cdot \nabla \mathbf{u}$$

1.3 Mass conservation

Because matter is neither created nor destroyed, the mass density ρ satisfies

$$\partial \rho / \partial t + \nabla \cdot (\rho \mathbf{u}) = 0$$
, or equivalently $D\rho / Dt + \rho \nabla \cdot \mathbf{u} = 0$

The quantity $\rho \mathbf{u}$ is called the mass flux. For an incompressible fluid, the density of each material element is constant, and so $D\rho/Dt = 0$. Hence

$$\nabla \cdot \mathbf{u} = 0.$$


In this course, we shall also restrict attention to fluids that are incompressible and have uniform density, so that ρ is independent of both **x** and *t*.

For planar flows, the condition $\nabla \cdot \mathbf{u} = 0$ is automatically satisfied by $\mathbf{u} = (\psi_y, -\psi_x, 0)$, with streamfunction $\psi(x, y)$.

1.4 Kinematic boundary condition

Applying mass conservation to a region close to a boundary S, we have

$$\rho \mathbf{u}^{-} \cdot \mathbf{n} = \rho \mathbf{u}^{+} \cdot \mathbf{n},$$




i.e. the normal component of velocity must be continuous across S. In particular at a fixed boundary, $\mathbf{u} \cdot \mathbf{n} = 0$. Equivalently, if the moving boundary of a fluid is given by the equation $F(\mathbf{x}, t) = 0$, then since the surface consists of material points, DF/Dt = 0. This form of the boundary condition is sometimes more convenient for free-surface problems.

1.5 Momentum conservation

On the assumption that the only surface force that acts across a material surface $\mathbf{n}dS$ is given by a pressure $p(\mathbf{x}, t)$ as $-p\mathbf{n}dS$, then Newton's equation of motion is

$$\rho \frac{D\mathbf{u}}{Dt} = -\nabla p + \mathbf{F}(\mathbf{x}, t),$$



where $\mathbf{F}(\mathbf{x}, t)$ is the force per unit volume (called 'force density' or 'body force', e.g. gravity $\rho \mathbf{g}$) that acts on the fluid. This is Euler's equation.

1.6 Dynamic boundary condition

On the same assumption, momentum conservation applied to a region close to the boundary S gives (in the absence of surface tension)

$$-p^{-}\mathbf{n}=-p^{+}\mathbf{n},$$

and thus the pressure must be continuous across S.

In this course, we abandon the *inviscid* assumption of §1.5 & §1.6, and will include tangential frictional forces (stresses) across material surfaces to derive new equations for momentum conservation with new boundary conditions. We will find that there is a viscous contribution to the normal force on a surface.

1.7 Example: Potential flow past a circular cylinder

The steady Euler equation with $\mathbf{F} = \mathbf{0}$ is satisfied by a potential flow $\mathbf{u} = \nabla \phi$ with $\nabla \cdot \mathbf{u} = \nabla^2 \phi = 0$, and pressure from Bernoulli $p + \frac{1}{2}\rho u^2 = \text{const.}$

The solution with $\phi \sim Ux = Ur \cos \theta$ as $r \to \overline{\infty}$ (i.e. uniform stream of velocity U) and $\mathbf{u} \cdot \mathbf{n} = \partial \phi / \partial r = 0$ on r = R is

$$\phi = U(r + R^2/r)\cos\theta,$$

with associated streamfunction $\psi = U(r - R^2/r) \sin \theta$.

1.8 Other important ideas and results

- Introduction to viscosity and shear stresses
- Simple unidirectional flows (e.g. Couette)
- Introduction to vorticity
- Potential flows
- Bernoulli's equation [Integral form of Euler]
- Water waves
- Fluid dynamics in a rotating frame
- Shallow-water equations